


METAL EXPANSION JOINT

Floor to Floor | Floor to Wall


25 - 50 mm (1 - 2") Expansion Gaps

Megatec 380 : A01-A02

Megatec 380 : A01



Megatec 380 : A02



Expansion Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B (mm)	Movement Capacity (mm)		Eurocode Rating				Product Dimensions Height		Sightline A (mm)	Blockout C (mm)	Product Number
		±	[Total]					H1 (mm)	H2 (mm)			
Floor - Floor	25	± 12	[25]	-	-	-	-	4	-	60	-	380-A01-025
	50	± 25	[50]	-	-	-	-	4	-	90	-	380-A01-050
Floor - Wall	25	± 12	[25]	-	-	-	-	4	40	50	-	380-A02-025
	50	± 25	[50]	-	-	-	-	4	40	100	-	380-A02-050

Features

Surface

Americans with Disabilities Act (ADA) compliant across the entire movement cycle

Movement

Good movement capacity

ASTM E-1399 Class I: Thermal
Class II: Wind

Traffic Frequency per day

				
≤ 5,000	-	-	-	-


System Options

Gap width(s)	25, 50 mm
Height(s)	4 mm
Metal type(s)	6063 T5 & T6 Aluminium
Seal colour(s)	No seal used
Fire barrier	120-240 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt

METAL EXPANSION JOINT

Floor to Floor | Floor to Wall
25 - 50 mm (1 - 2") Expansion Gaps

Megatec 380 : A01-A02



APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets

www.vexcoltindia.com